

TECHNICAL DATA SHEET

PRODUCT DESCRIPTION:

STA'-PUT® ST172 is a non-flammable solvent cleaner used for cleaning adhesive over-spray and adhesive spray equipment.

ADVANTAGE:

- Effective as a General Cleaner
- Quick cut action
- Leaves no Film

TYPICAL PROPERTIES:

Property	Typical Value
Solvent:	Methylene Chloride, Trichloroethylene*
Shelf Life:	1 year from Date of Manufacture**
Color:	Clear
Flash Point:	N/A
Weight / Gallon	11.2 lbs./ gallon
VOC Content	1497.7 g/L (EPA Method 24)
Formaldehyde	No urea formaldehyde added during adhesive manufacturing

* Reports have associated repeated and prolonged occupational exposure to solvents with permanent brain and nervous system damage
** The shelf life for an unopened container of this adhesive stored at temperatures between 60°F (15.6°C) and 95°F (35°C) is 1 year from date of manufacture. Store out of direct sunlight in a cool, well-ventilated area. Avoid storing container directly on the floor or against an outside wall

APPLICATION INFORMATION

- In wiping adhesive smears off work, avoid flooding the area to be cleaned since excess solvent can work into seams, softening the bond line, and causing delamination.
- Use a cloth that is saturated with solvent but not dripping.
- Keep solvent contact at the edges and seams of the lamination to a minimum to avoid the danger of softening the bond line.
- The sooner the smears are removed the easier it is to remove them.
- DO NOT THIN.

ATTENTION:

- Empty container remains hazardous until all flammable vapors, which may explode upon ignition, are gone from residue and container. Observe all labeled hazard precautions. Do not cut, puncture, or weld while hazard exists.
- Do not reuse empty container. Recycle, or dispose of, according to all federal, state, and local regulations. Follow solvent manufacture's recommendations and instructions for safe handling.
- This product contains an extremely fast evaporating solvent in order to provide maximum safety, versatility and performance. This could result in pressure build-up in the container, particularly at elevated temperatures.
- DO NOT OPEN CONTAINER UNLESS THE TEMPERATURE OF THE CONTENTS IS BELOW 100°F. DO NOT STORE WHERE THE TEMPERATURE CAN EXCEED 100°F.

EXCLUSION OF WARRANTIES:

INSTALL AS DIRECTED ON STAPUT® PRODUCT DATA SHEET. USER DETERMINES SUITABILITY FOR INTENDED USE AND ASSUMES ALL RISK AND LIABILITY. THIS PRODUCT IS SOLD "AS IS." EXCEPT AS REQUIRED BY LAW, THERE ARE NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, WITHOUT LIMITATION, WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. IF TERMS ARE NOT ACCEPTABLE, RETURN UNOPENED PRODUCT TO PLACE OF PURCHASE. DAMAGES IN EXCESS OF THE PURCHASE PRICE OF THESE PRODUCTS.

KEEP OUT OF REACH OF CHILDREN
FOR PROFESSIONAL OR INDUSTRIAL USE ONLY
USE ONLY WITH APPROVED EQUIPMENT

Complete technical information is available from ITW Polymers Sealants North America, Inc